

Monitor. Integrate. Alert. Peace of Mind.

Applications

- Ideal for smaller contained areas like air conditioner condensate pans.
- Frequently used in facilities with pumps, chillers, boilers, and water control valves.

Key Features

- Monitor up to 300 feet of sensing cable and spot detectors
- Lightweight, compact design
- Plug and play installation
- Adjustable leak alarm sensitivity
- Local audible and visible alarm annunciation
- Integrate into a larger system via leak and fault relay outputs



Reliable Leak Detection In A Compact Package

RLE's most cost effective controller, the LD310 is easy to install and provides reliable leak detection as either a stand-alone device or integrated into a larger BMS platform.

What Sets RLE's LD310 Apart?

- **Zone leak detection** system alarms when water comes into contact with the attached sensing cable or spot detector. It is the right fit for spaces where sensing cables and spot detectors are visible so leaks can easily be located.
- **A supervised system**, the controller continuously monitors the cable for leaks, breaks, and disconnects and sends an alarm notification when one is detected.
- **Local alarm annunciation.** Onboard audible and visible alarms notify users of leaks and faults in real time.
- **Patented leak detection technology.** Our cables dry and reset quickly so they're ready to detect the next issue.

LD310 • Compatible with all RLE SeaHawk sensing cables and the SD-Z and SD-Z1 spot detectors

Product Codes	
LD310	Single zone leak detection controller with audible alarm. Includes LC-KIT for use with SC, SC-ZH, SD-Z. Requires PSWA-DC-5 or WA-DC-5-ST.
LD310-M	Single zone leak detection controller with audible alarm. Includes LC-KIT-M for use with SC-C. Requires PSWA-DC-5 or WA-DC-5-ST.
PSWA-DC-5	Power adapter; isolated 100-240VAC to 5VDC, 1.6A. Barrel connector. Striped lead is positive. Includes type A blade.
WA-DC-5-ST	Power adapter; 100-240V to 5VDC. Type A plug. Stripped end.

Technical Specifications	
Power	Requires an isolated power supply. 5VDC (±10%) Isolated @ 100mA max.; requires RLE power supply PSWA-DC-5 or WA-DC-5-ST (not included)
Included Accessories	Leader cable and EOL terminator
Sensing Cable Cable Input Maximum Length Detection Response Time	One zone leak detection; Compatible with all SeaHawk sensing cables and SD-Z and SD-Z1 spot detectors Requires 15ft (4.57m) leader cable and EOL (included) 300ft (91m) of sensing cable <20sec; 10sec typical
Relay Output	2 Form C alarm relays (leak and fault); 1A @ 24VDC, 0.5A resistive @ 120VAC; configurable as supervised or non-supervised
Panel Alarm Notification Audible Alarm	85dB @ 10cm (min) Indicates cable break or leak detected
Visible Alarm	Bi-color LED Normal Operation - Green Cable Fault - Flashing Orange Leak Detected - Flashing Red
Push Button Switch Push Once Push and Hold for 5 Seconds	Silence audible alarm Initiates system test, resets system, clears all active alarms
Operating Environment Temperature Humidity Altitude	32° to 122°F (0° to 50°C) 5% to 95% RH, non-condensing 15,000ft (4,572m) max.
Storage Environment	-4° to 158°F (-20° to 70°C)
Dimensions	4.4"L x 2.5"W x 1.5"H (11.2cmL x 6.4cmW x 3.8cmH)
Weight	0.2lb (0.1kg)
Mounting	Free standing, zip ties, screw and keyhole – spaced 2.5" (6.4cm), junction box – 2 screws spaced 3.28" (8.3cm)
Certifications	CE; ETL listed: conforms to UL 61010-1, EN 61010-1; RoHS compliant

